

## Arpool Linear Surface

### TECHNOLOGY



#### Flow Sense

A built-in protector against power-related issues, ensuring lasting performance and safety.




#### Split & Seal

Uses protective polymers to shield Filix products from water and moisture, boosting durability and resilience.



#### Heat Sense


Automatically reduces LED power at high temperatures, ensuring longevity and safety in Filix products.





## Arpool Linear Surface

Specification Sheet



**UL STD 676** swimming pool rated  
**CSA C22.2#89** swimming pool rated  
**IP68**

### LUMINAIRE FEATURES

#### Design and Application

- Wall and floor installation
- Infinity pools and swimming pools complexes

#### Mechanical details

- IK10 crystal-clear tempered glass, 10mm (0.39") thick
- IP68, rated for permanent submersion
- Maximum installation depth up to 5m (16')
- AISI316L stainless steel body
- Suitable for chlorine and marine environments
- Supplied with 3m(10') oil and water resistant feed cable as standard
- Surface installation secured with A4 grade screws
- Galvanic protection

#### Electrical details

- LED Lifetime TM-21 @ 105°C  
L80(14K) = 81,600 hours
- Operating temperature: -20°C (-28°F) to +50°C (122°F)
- LED CRI: >85
- 3 step MacAdam
- Remote power supply
- Low voltage operation

#### Sustainability

- Recyclable materials

#### Controls

- DMX, with compatible LED power supply
- DALI, with compatible LED power supply
- 0-10V, with compatible LED power supply
- Mains, with compatible LED power supply

#### Integrated systems

- Split & Seal
- Flow Sense
- Heat Sense

#### Links & Downloads

- [List of available drivers](#)
- [Voltage drop calculator](#)
- [Fixture installation manual](#)
- [CAD files](#)
- [IES-LTD data](#)

W45mm X H82mm X L320/620mm



# Arpool Linear Surface

## ORDERING INFORMATION

### MODEL

ALS

### LENGHT

320

- 320mm (12,6")

620

- 620mm (24,4")

### POWER

L

- L - 39W/m, 2700/3000/4000K, 3360lm/m

H

- H - 63W/m, 2700/3000/4000K, 5920lm/m

- L - 47W/m, RGBW

### COLOR TEMP.

27

- 27 - 2700K

30

- 30 - 3000K

40

- 40 - 4000K

TW

- TW - Tunable white (2200-4000K)

RGBW

- RGBW (W 4000K)

### OPTICS

SP

- SP - Spot - 17° x 17°

FL

- FL - Flood - 31° x 31°

GR

- GR - Graze - 14° x 40°

GR20

- GR20 - 14° x 40°/tilt 20°

GRW

- GRW - Graze - 10° x 60°

SPX

- SPX - Spot - 17° + hex

FLX

- FLX - Flood - 31° + hex

GRX

- GRX - Graze - 14° x 40° + hex

GR20X

- GR20X - 14° x 40°/tilt 20° + hex

GRWX

- GRWX - Graze - 10° x 60° + hex

### VOLTAGE

12

- 12 - 12VDC fixture voltage

24

- 24 - 24VDC fixture voltage

### OPTIONS

3

- 3\* - standard feed cable 3m (10')

6

- 6 - luminaire supplied with 6m (20') feed cable

9

- 9 - luminaire supplied with 9m (30') feed cable

20

- 20 - luminaire supplied with 20m (65') feed cable

### GLARE CONTROL

1

- 1 - Half moon



# Arpool Linear Surface

## MANDATORY ACCESSORIES

### Power supplies

DRIVERS

[LINK](#)

- [List of available drivers](#)

## OPTIONAL ACCESSORIES

### Various Accessories



WWD

- WWD - Adjustable waterproof wall duct



## Arpool Linear Surface INSTALLATION DETAILS

### Fixture



Made out of AISI316l stainless steel with additional passive coating, this luminaire is suitable for use in marine and chlorine environments. The standard luminaires are equipped with water and oil-resistant cables in various standard lengths. With integrated systems such as Flow Sense, Heat Sense, and Split & Seal, the luminaire has all the needed protective barriers.


Note:  
For details on specific depths, tiling thickness and other please refer to both Installation instructions for fixture and housing.



# Arpool Linear Surface

## ACCESSORIES

Adjustable waterproof wall duct



Note:  
For details on specific depths, tiling thickness and other please refer to both Installation instructions for fixture and housing.




## Arpool Linear Surface

### MANDATORY ACCESSORIES

#### Power supply


A LED power supply, is an electrical device designed to control the power supplied to an LED or an array of LEDs. It plays a critical role in LED lighting systems as LEDs demand a specific type and level of electrical current or voltage for optimal operation. It's important to note whether a constant current or constant voltage LED power supply is required. The power supply should be installed in a dry and easily accessible area.



### OPTIONAL ACCESSORIES

#### Waterproof wall duck

Ensures a secure, watertight transition between the water body and the concrete shell, with adjustable features to accommodate different wall thicknesses.





# Arpool Linear Surface

## GLARE CONTROL

### Internal glare control:

#### Hex louvre



Provides low glare control with 45% less lumen output than product without louvres. Best for use when there is no need for segment beam cut off such as in half moon

#### Half moon

Provides glare control by reducing lumen output and implementing a light beam cut-off, resulting in a 50% reduction in stray light and minimized light dispersion in undesirable directions.

#### Honeymoon

Combines the benefits of Hex Louvre and Halfmoon, offering both reduced glare and controlled light dispersion for comprehensive glare management.









# Arpool Linear Surface

## OPTICS



**Spot**  
Angle: 17°x17°  
Delivered lumen: 3360lm/m





**Flood**  
Angle: 31°x31°  
Delivered lumen: 2990lm/m





**Graze**  
Angle: 14°x40°  
Delivered lumen: 3300lm/m



**Graze Wide**  
Angle: 10°x60°  
Delivered lumen: 2450lm/m



**GR20**  
Angle: 14°x40° tilt 20°  
Delivered lumen: 3200lm/m



### Notes

- Light output values based on 40W/m and 3000K product



## Control

### ON/OFF SYSTEM TOPOLOGY

#### Integrated systems:


- Heat Sense
- Flow Sense
- Split & Seal

#### System components

- Wiring and additional accessories leading up to the product feed cable are the responsibility of others.
- Housing and necessary accessories that are marked as mandatory must be ordered separately

#### System topology

- In the system design, any of the following system topologies can be utilized: line wiring, star wiring, or tree wiring.



#### Addressing & dimming notes

- ON/OFF system does not allow device addressing
- Dimming of the product not available in this system

#### Segment length and limitations

- All wire splicing should be performed in a dry area to ensure a proper connection.
- Used in single colour applications

#### Fault tolerance

- If one product fails, the rest of the system continues to work.



## Control

### 0-10V SYSTEM TOPOLOGY

#### Integrated systems:


- Heat Sense
- Flow Sense
- Split & Seal

#### System components

- The 0-10V system, wiring and additional accessories leading up to the product feed cable are the responsibility of others.
- Housing and necessary accessories that are marked as mandatory must be ordered separately

#### System topology

- In the system design, any of the following system topologies can be utilized: line wiring, star wiring, or tree wiring.



#### Addressing & dimming notes

- Without 0-10V dimmable power supply product can not be controled
- Individual device addressing can be achieved by connecting each product to a separate output channel of the 0-10V dimmable power supply.
- Logarithmic and linear dimming options depend on the 0-10V dimmable LED power supply
- The dimming range is determined by the 0-10V dimmable LED power supply

#### Segment length and limitations

- The minimum controllable segment is one product.
- All wire splicing should be performed in a dry area to ensure a proper connection.
- Used in single colour applications

#### Fault tolerance

- If the LED driver is source type and in the case the control line doesn't have power the light fitting will turn at 100%. in the opposite case where the LED power supply is sink type, light will not work.
- If one product fails the rest of the system continues to work.



## Control

### DALI SYSTEM TOPOLOGY

#### Integrated systems:


- Heat Sense
- Flow Sense
- Split & Seal

#### System components

- The DALI system, wiring and additional accessories leading up to the product feed cable are the responsibility of others.
- Housing and necessary accessories that are marked as mandatory must to be ordered separately

#### System topology

- In the system design, any of the following system topologies can be utilized: line wiring, star wiring, or tree wiring.



#### Addressing & dimming notes

- Without a DALI dimmable power supply, the product cannot be controlled.
- Individual device addressing (short address) and group addresses for up to 16 groups can be achieved by connecting each group of products to a separate output channel of the DALI dimmable power supply. A broadcast address targets everything on the line of the DALI dimmable LED driver.
- Logarithmic and linear dimming options depend on the DALI dimmable LED power supply.
- The dimming range is determined by the DALI dimmable LED power supply.

#### Segment length and limitations

- The minimum controllable segment is one product.
- A DALI dimmable power supply cannot control fittings individually unless they are connected to separate channels of a DALI dimmable power supply.
- All wire splicing should be performed in a dry area to ensure a proper connection.
- Suitable for both single-color and multi-color applications.

#### Fault tolerance

- If one product fails, the rest of the system continues to work.



## Control

### DMX SYSTEM TOPOLOGY

#### Integrated systems:


- Heat Sense
- Flow Sense
- Split & Seal

#### System components

- The DMX system, wiring and additional accessories leading up to the product feed cable are the responsibility of others.
- Housing and necessary accessories that are marked as mandatory must be ordered separately

#### System topology

- In the system design, any of the following system topologies can be utilized: line wiring, star wiring, or tree wiring.



#### Addressing & dimming notes

- The minimum controllable segment is one product.
- A DMX dimmable power supply cannot control fittings individually unless they are connected to separate channels of a DMX dimmable power supply.
- In a parallel connection of multiple fittings, the maximum distance between the LED power supply and the last fitting in line is limited to the maximum allowed voltage drop.
- In a serial connection of multiple fittings, the maximum length of a cable loop is 50 meters, and the electrical circuit size is limited by power supply ratings, such as output voltage range.
- All wire splicing should be performed in a dry area to ensure a proper connection.

#### Segment length and limitations

- Without a DMX dimmable power supply, the product cannot be controlled.
- Individual device addressing (short address) and group addresses can be achieved by connecting each product or a group to a separate output channel of the DMX dimmable power supply.
- Logarithmic and linear dimming options depend on the DMX dimmable LED power supply.
- The dimming range is determined by the DMX dimmable LED power supply.
- Suitable for both single-color and multi-color applications.

#### Fault tolerance

- If one product fails, the rest of the system continues to work.