



RDP100 Paver

Specification Sheet



IP67

LUMINAIRE FEATURES

Design and Application

- Architectural and landscape lighting
- Recessed floor installation
- Gravel, soil or concrete installation
- UL STD 1598, IP67, Wet location, drive over rated 1500 kg (3300lb)

Performance

- · IK10, Tempered glass, frosted
- Aluminium construction fixture body
- Stainless steel type 304 flange
- Snap in installation with no exposed hardware
- Lifetime TM-21 @85C L70(10K)>60000
- Supplied with oil and water resistant
 0.3m (1') feed cable as standard
- CRI: > 85
- 2 Step MacAdam

Safety

- Remote power supply
- · Low voltage operation
- · Recessed installation

Sustainability

• Recyclable material

Installation housing

- RD100C Trim
- RD100T Trimless

Accessories


• 104853 - Removal tool

Power supplies


- List of proposed power supplies that are to be ordered separately.
- Click $\underline{\text{here}}$ for list of available drivers.
- Click here for voltage drop and distances.

FILIX

Trim (TM)



Trimless(TS)



Click <u>here</u> to download fixure installation manual.

Click <u>here</u> to download housing installation manual.

Click here to download CAD file.

Click $\underline{\text{here}}$ to download IES-LTD data.





RDP100 Paver

ORDERING INFORMATION

FRDP100

INSTALATION

TM

• Trim (TM)

TS

• Trimless (TS)

POWER

L

• L - 2,9W, 2700K - 3000K, 100 lm

н

• H - 4,8W, 2700K - 3000K, 160 lm

• H -5,6W RGBW (W 3000K)

COLOR TEMP.

27

• 27 - 2700K

30

• 30 - 3000K

RGBW

• RGBW (W 3000K)

OPTICS

LL

• LL - 120° even illumination

VOLTAGE

24

• 24 - 24 VDC fixture voltage

OPTIONS

3

• 3 - luminaire supplied with 3m (10') feed cable

6

• 6 - luminaire supplied with 6m (20') feed cable

9

• 9 - luminaire supplied with 9m (30') feed cable







RDP100 Paver


INSTALLATION DETAILS


Installation housing - RD100C - Trim installation

Installation housing - RD100T - Trimless installation









Note:

For details on specific depths, tiling thickness and other please refer to both Installation instructions for fixture and housing.